





Specification

Product Name		LED Down Light	Image	
Model No.		BM-DL-7W		
Optical characteristic	LED source	Bridgelux	Photometric data	
	LED type	1W High power		
	CCT	6000-6500K		
	LED quantity	7PCS		
	Cover Type	PMMA		
	Luminous efficiency	90LM/W		
	Luminous Flux	>650LM		
	CRI	Ra≥75		
	Beam angle	30° 60°		
Electricity characteristic	Input voltage/Current	AC85V-277V/ 0.031A-0.101A	LUX	
	Frequency	50-60Hz		
	Output voltage	21-28V		
	Output current	300ma±3%		
	Power	8.6W		
	LED Power	7W		
	Power efficiency	≥85%		
	Power factor	>0.9		
	Dimmable	Optional		
Other characteristic	Surface temperature	55℃(environment temperature31℃)	Structure	
	Operating temperature	-35℃-- +55℃		
	Installing method	Screw		
	Work humidity	5%-95%RH		
	Storage temperature	-40℃-- +65℃		
	Equivalent Incandescent lamp	60W		
	IP rate	IP64		
	LED lifespan	>40000h		
	Casing material	AL		
	Weight	387g		
	Size	Φ106*70mm		
	Opening Size	Φ98mm		
	Box size	1pcs/box 110×110×75mm		
	Carton size	32pcs/carton460×460×160mm		